



About this product

weber.prim Plaskey WB250 is a cement-based primer and surface preparation material which is suitable for interior and exterior use. This product is designed for wall and floor applications. **weber.prim Plaskey WB250** is specially formulated to provide excellent water resistance and all purpose surface preparation for tiling.

Technical data

Shelf life	9 months in dry moderate conditions
Pot life	1 hour
Coverage	24m ² per 20 kg bag at 1,5 mm - 2 mm thickness.
Curing	Allow to dry for least 24 hours before applying tiling, screeds and plasters.

Packaging

weber.prim Plaskey WB250 is supplied in 5 kg and 20 kg bags.

Use

- It is suitable for interior and exterior use.
- Suitable for wall and floor applications.
- **weber.prim Plaskey WB250** is specially formulated to provide excellent water resistance and all purpose surface preparation for tiling.
- It can be applied onto friable, timber, smooth, previously painted and gypsum plastered surfaces.
- **weber.prim Plaskey WB250** must be mixed with **weber.ad Key-It WB117**.

Features and benefits

- All purpose surface preparation for tiling
- Waterproofing properties
- Easy to apply

Precaution

Wear rubber gloves. In the event of contamination, rinse thoroughly with cold water. Seek medical assistance if irritation or discomfort persists.

Safety instructions

Contains cement, which is alkaline when wet and can cause skin irritation. Use eye protection and gloves and avoid prolonged skin contact. Avoid inhalation of dust. Wash skin contamination away with warm soapy water. Remove splashes to the eyes by prolonged irrigation and consult a doctor. Do not ingest.

General

- **weber.prim Plaskey WB250** should not be applied externally when there is a risk of rain or frost within six hours after application.
- Equipment should be cleaned with water immediately after the application has been completed.

Mixing and application

1. Gradually mix 20 kg of **weber.prim Plaskey WB250** to not more than 10 litres of **weber.ad Key-It WB117**
2. Mix thoroughly to a paintable consistency
3. For increased plasticity allow mix to gel for 5 minutes
4. Remix before use
5. Apply with a builders block brush or a large paint brush to ± 2 mm thickness ensuring that full coverage is achieved
6. Allow to dry for at least 24 hours before tiling commences

Guarantee

We agree that **Weber** products meet the product specifications and will be free from any defect. Any guarantee with regard to the performance of **Weber** products will be subject to its professional and practical application of **Weber** products in accordance with our instructions and specifications.

However, we have no influence over specific site conditions and therefore, if in doubt, the user should first carry out sufficient tests to ensure that the product is suitable. In special cases, obtain advice. Should our product prove defective, we undertake to replace any defective material. This guarantee will fall away in the event of **Weber** products being contaminated by the addition of sand, cement or substance other than recommended by us.

Technical services

Weber has a team of experienced advisors available to provide technical support.
Technical helpline: 08600 Weber (93237) or visit www.weber-tylon.co.za