

About this product

Weber Pool Primer is a cement-based primer and surface preparation material which is suitable for pool interior use. This product is designed for pool wall and floor applications. **Weber Pool Primer** is specially formulated to provide excellent bonding and all-purpose surface preparation for pool painting and pool re-painting of a previously marbelite plastered and existing painted pools.

Technical Data

Shelf life	12 months in dry moderate conditions
Pot life	1 hour
Coverage	Coverage is approximately 15m ² per 15 kg twin pack at 1,0 mm – 2,0 mm thickness.
Curing	Allow to dry for least 24 hours before applying pool paint.

Pool Primer Components

The following are included in the system

- 10 kg Pool Primer Compound (Part A)
- 5 Liter Pool Primer Emulsion (Part B)

Packaging

Weber Pool Primer is supplied in 10 kg Pool Primer Compound Part A and 5-liter Pool Primer Emulsion Part B in a 20L bucket.

Use

- It is suitable for pool interior use.
- Suitable for pool wall and floor applications and the surface should be rough to the touch after application.
- **Weber Pool Primer** is specially formulated to provide excellent bonding and all-purpose surface preparation for pool painting and pool re-painting of marbelite plastered and existing painted pools.
- It can be applied onto smooth, previously painted and plastered surfaces. Not suitable for filling of cracks on the pool. Use ABE/Weber Pool Repair to close the cracks.????
- **Pool Primer Compound (Part A)** must be mixed with **Pool Primer Emulsion (Part B)** completely. Do not part mix the paint.
- **Weber Pool Primer is recommended to for use with Weber Pool Paint but can also be used with other pool paint products in the market suitable for marbelite pools**

Features and Benefits

- All purpose surface preparation for pool applications
- Waterproofing properties
- Easy to apply for re-painting over existing pool paint, need to strip off the old pool paint and also saves time on stripping the old pool paint

Pre-caution

Wear rubber gloves. In the event of contamination, rinse thoroughly with cold water. Seek medical assistance if irritation or discomfort persists.

Safety Instructions

Contains cement, which is alkaline when wet and can cause skin irritation. Use eye protection and gloves and avoid prolonged skin contact. Avoid inhalation of dust. Wash skin contamination away with warm soapy water. Remove splashes to the eyes by prolonged irrigation and consult a doctor. Do not ingest.

General

- **Weber Pool Primer** should not be applied when there is a risk of rain or frost within 24 hours after application.
- Do not apply in damp or wet conditions.
- Do not apply in temperature below 5°C or above 30°C
- **Preferably start to apply in the morning to allow the primer enough time to cure and the early start of pool paint application the following day.**
- Equipment should be cleaned with water immediately after the application has been completed.
- Correct surface preparation is critical to ensure the proper performance of **Weber Pool Primer**. Please follow the instructions below carefully.

Surface preparation

- Prepare a solution of 1-part hydrochloric acid and 3 parts water in a plastic bucket. Put the water in the bucket first and then add then acid while stirring. Be sure to wear gloves and eye protection.
- Apply the acid mix to the surface using a block-brush
- Scrub the surface vigorously using a wire brush.
- Flush with clean water, and flush with at least 3 litres of water per square meter scrubbing to happen for a minimum of 3 minutes. Leave to dry for at least 3 hours.
- Remove high spots and calcium build-up using 80 grit sandpaper. Be sure to remove any loose materials. The surface should be very rough to the touch. If this is not the case, repeat the acid washing procedure described above.
- **Check if there are any cracks before applying Pool Primer and if there are any cracks use ABE/Weber Pool Repair???**
- Brush and vacuum the entire surface to remove dust and debris. Dust on the surface will impede the adherence of the Pool Primer.
- Mask all areas where there is a risk of splashing and staining and where straight edges are required.

Mixing and Application

1. Gradually mix 10 kg of **Pool Primer Compound (Part A)** to 5 liters of Pool Primer Emulsion Compound (Part B). **The entire contents of Part A should be mixed with the entire contents of Part B in one operation. Do not part mix.**
2. Mix thoroughly to a paintable consistency using mechanical mixer
3. Allow the mixture to mature for 5 minutes
4. Re – mix thoroughly before use
5. Ensure that the substrate is clean and dust free
6. Apply with a builders block brush or a large paint brush from 1mm – 2mm thickness ensuring that full coverage is achieved
7. Allow to dry for at least 24 hours before painting commences

Pool Paint Application

- Please Refer to Pool Paint Application Instructions
- **Pool paint can be used without the use of the pool primer, however if there is existing pool paint in the pool it needs to be completely stripped off before application.**
- **Pool primer is recommended for use as there will be no need to strip off the old pool paint**

Guarantee

We agree that **Weber** products meet the product specifications and will be free from any defect. Any guarantee with regard to the performance of **Weber** products will be subject to its professional and practical application of **Weber** products in accordance with our instructions and specifications.

However, we have no influence over specific site conditions and therefore, if in doubt, the user should first carry out sufficient tests to ensure that the product is suitable. In special cases, obtain advice. Should our product prove defective, we undertake to replace any defective material. This guarantee will fall away in the event of **Weber** products being contaminated by the addition of sand, cement or substance other than recommended by us.

Technical services

Weber has a team of experienced advisors available to provide technical support.
Technical helpline: 08600 Weber (93237) or visit www.weber-tylon.co.za

Saint-Gobain Construction Products SA (Pty) Ltd
300 Janadel Ave, Halfway House, Midrand, South Africa
Tel: +27 11345-5300
Sales: 08600 Weber (93237) or visit www.weber-tylon.co.za
Products are sold subject to the Standard Conditions of sale



To the best of our knowledge and belief, this information is true and accurate. As the conditions of use and any labor involved are beyond our control, the end-user must satisfy himself by prior testing that the product is suitable for his specific application

